



Certified to NSF/ANSI Standard 50

| FILTER MODEL | FILTER FLANGE | OVERALL LENGTH | FILTER AREA (SQ.FT.) | DESIGN FILTER RATE @ 15 GPM / SQ.FT. MAX. |
|--|-------------------------------|----------------|----------------------|---|
| 160-205 | 8" | 209" | 81.6 | 1224 GPM |
| MEDIA REQUIREMENTS - NUMBER OF BAGS (100 LB = 1 CUBIC FOOT) | | | | |
| BOTTOM LAYER | 1/4" X 1/2" STONE | | 25 BAGS | |
| SECOND LAYER | 1/8" X 1/4" STONE | | 20 BAGS | |
| THIRD LAYER | 6-20 / 1.0-1.2 MM / GP#2 SAND | | 24 BAGS | |
| TOP LAYER | 20-30 / 0.45-0.55 MM SAND | | 101 BAGS | |

| | | |
|----------------------------------|-------------------------------|-----------------------|
| MER-MADE FILTER | | |
| PO Box 306 Denmark, SC 29042 | | |
| P: 803-793-4265 F: 803-793-4332 | | |
| 160-205 Filter Dimensions | | |
| Sand Filters | Date: 12-1-20 Dr. By: C.S. | Dwg. No. T-14319 O |