



NOTES

1. STRAINER BODY: FIBERGLASS CONSTRUCTION USING ISOPHTHALIC POLYESTER RESIN AND A .100" THK. CORROSION LINER USING ONE LAYER C GLASS AND TWO LAYERS CHOPPED STRAND MAT.
2. LID: CLEAR ACRYLIC
3. TOGGLE BOLTS: STAINLESS STEEL
4. HAND KNOBS: ABS WITH BRASS INSERTS
5. O-RING: ETHYLENE PROPYLENE
6. BASKET: 316 STAINLESS STEEL WEDGE WIRE, 3/16" SQUARE OPENING

-INLET AND OUTLET FLANGES SHALL HAVE 150#
ANSI STANDARD DRILL PATTERNS



CERTIFIED FOR PRODUCTION									
BY: _____ DATE: _____									
MER-MADE, INC.									
TOLERANCES UNLESS OTHERWISE SPECIFIED									
MACHINED DIMENSIONS:									
X.X ± .020 FINISH: 125/									
X.XX ± .010 ANGLES: ± 2									
X.XXX ± .005 RADII: ± .03									
FRACTIONAL DIMENSIONS:									
1/X ± 1/8									
REMOVE ALL BURRS AND BREAK ALL SHARP EDGES: .016 x 45°									
REV	DESCRIPTION								
DATE									
SCALE: NTS	DATE: 04/23/18	Sheet: 1	OF	1					
SIZE		DWN BY: SJV		DWG NO.					
B		CHK BY:		M-0167		REV			
						R0			
8" x 3" T-STYLE ECCENTRIC REDUCING BASKET STRAINER									
MER-MADE® PO BOX 306 DENMARK, SC 29042 P:803-793-4263 F:803-793-4265									